

LEDlight flex 12 8p High Efficiency

- LED strips for highest demands
- ideal for applications with high daily operating time
- long light lines possible with only one in-feed due to double layer FPC
- very long service life L90/B10 > 60,000 h at Tc < 80 °C
- current regulation by IC for constant brightness over the entire light line
- with reverse polarity protection and TVS surge protection diode
- with high-quality 3M double adhesive tape



Please observe the installation and safety instructions at <https://www.barthelme.de/content/en/manuals.aspx> !

Note re light sources/EPREL: Our LED reels are not subject to classification according to the currently valid regulations. An LED reel contains interconnected light sources, the number and energy efficiency class of which are listed in the data sheet.

PHOTOMETRIC DATA



	50407629	50407625	50407628	50407633	50407627	50407634	50407615
Typ. color temperature	2200 K	2500 K	2700 K	3000 K	3500 K	4000 K	5700 K
Light color	super warm white		warm white	white		cold white	daylight
Typ. luminous flux per meter	580 lm/m	640 lm/m	831 lm/m	860 lm/m	857 lm/m	886 lm/m	927 lm/m
Efficiency	108 lm/W	120 lm/W	156 lm/W	161 lm/W		166 lm/W	174 lm/W
Built-in light source	C50007629	C50007625	C50007628	C50007633	C50007627	C50007634	C50007615
Number of light sources	84						
EEC of built-in light source	F	E	D				C
Typ. color rendering index	84						
LED beam angle	120 °						
Lifetime L90/B10	>60.000 h						

ELECTRICAL DATA

	50407629	50407625	50407628	50407633	50407627	50407634	50407615
Operating voltage	24 V DC						
Typ. operating current	1,68 A						
Typ. power	40,3 W						
Typ. power per meter	5,3 W/m						

MECHANICAL DATA

	50407629	50407625	50407628	50407633	50407627	50407634	50407615
Length stripe	7560 mm						
Width stripe	8 mm						
Height stripe	1,4 mm						
Number of LEDs per cut	7						
Number of cuts	84						
Length per cut	90 mm						
Type of protection	IP 00						
	50007629	50007625	50007628	50007633	50007627	50007634	50007615
Color temperature	2200 K	2500 K	2700 K	3000 K	3500 K	4000 K	5700 K
EEC of built-in light source	F	E	D				C
Cut	Cut length 90 mm						

ORDER YOUR DESIRED INDIVIDUAL STRIP LENGTH [CUT]: The order quantity is a multiple of the smallest cutting length of the LED strip (cut). Ordering example: To order your required length of 210 cm of LEDlight flex High Efficiency 08 8 cool white (4000 K): 35x Art.-No. 50008634 (cut length 60 mm x 35 = 210 cm). If you re-quire varying strip lengths then please order each strip length as a separate position.


FURTHER DATA

	50407629	50407625	50407628	50407633	50407627	50407634	50407615
Max. operable length¹	12060 mm						
Storage temperature	-30° C ~ +80° C						
Max. temperature Tc²	80 ° C						


¹The value given applies to the application of the rated voltage at the first module section. When using a supply line, the maximum operable length changes depending on the supply line length and its cross section. At www.barthelme.de you will find an overview table for orientation.

² The Tc point is marked on each cut. This should be measured in the thermally stable state.

TECHNICAL DRAWING



USE IN PROFILES



weiß: LED-Punkte sichtbar, kein homogenes Lichtbild | white: LED dots visible, no uniform light distribution

blau: homogenes Lichtbild möglich | blue: uniform light distribution is possible

* = eine homogene Lichtlinie ist nur in Kombination mit einer hohen Abdeckung möglich | a uniform light line is only possible in combination with a high diffuser

@ max. Ta = 25 °C im Betrieb und Montagesituation Aufbau [Einbau bei CATania 30 UP und CATania 30 TB] ansonsten ggf. unzureichende Kühlung | @ max. Ta = 25 °C in operation and surface mounted installation [recessed installation with CATania 30 UP and CATania 30 TB] otherwise possibility of insufficient cooling
 Bitte beachten: Unzureichende Kühlung beschädigt den LED-Streifen! Verarbeitungshinweise zu LEDlight flex siehe www.barthelme.de | Please note: insufficient cooling will damage the LED strips! Processing notes for LEDlight flex see www.barthelme.de

NOTE

LEDs and the electronic components/devices required for their operation are wearing parts and can function for many years depending on use and location. In general, these products are subject to an aging process, the light output of LEDs decreases in the course of their operating life. The aging of LEDs is due to thermal influences. Our LEDs correspond to the operating life, which has e.g. a L90/B10 value. This means that the installed LEDs of a given type retain at least 90% of their luminous efficiency and a maximum of 10% of the installed LEDs can deviate from this. Thus, the decrease of the luminous effect of the LED within the above-mentioned scope within the operating life does not represent a defect according to the current state of technology.

Never glue the LED strip over a profile joint! Due to physical expansion or contraction of the profile due to temperature fluctuations, the LED strip can be damaged. This can be remedied by using the right parts for the solder pads at the joint and by using flexible connections, e.g. soldered flexible wire bridges or LED strip connectors.

The guarantee period for the product is 5 years and begins on the day of shipment. Reference is the date of the delivery bill. The guarantee period may differ for accessories.