

Adriano - Ground recessed spotlight 145 mm

230 V AC - stainless steel shield - IP67

- dimmable, high quality 230 V AC LED recessed floor spotlight for outdoor use
- robust aluminum luminaire with SUS 316 stainless steel shield
- asymmetrical beam angle (70° x 52°), ideal for facade illumination
- color temperature: 3000 K
- power supply included, dimmable via leading and trailing edge phase control
- easy installation due to direct connection to 230 V
- homogeneous light pattern with high color rendering CRI > Ra 90
- impact resistance grade IK10, walkable
- protection class IP67: complete protection against contact and dust; protection against submersion up to 30 minutes



LIGHT DATA

	62013070
Typ. color temperature	3000 K
Light color	white
LED beam angle	70x52 °
Typ. luminous flux	665 lm
Efficiency	40 lm/W
EEC of installed light source(s)	G
Typ. color rendering index	90
SDCM MacAdam	3

POWER DATA

	62013070
Operating voltage	230 V AC
Current consumption	73 mA
Typ. power	16,8 W

FURTHER DATA

	62013070
Length	155 mm
Diameter	145 mm
Mounting diameter	142 mm
Type of protection	IP 67
Indoor/Outdoor	Outdoor
Material	aluminium
Material shield	stainless steel
Cable termination	2m cable with free wire ends
Max. temperature Tc	85 ° C
Max. ambient temperature Ta	-20 ° C ~ +40 ° C
Lifetime L90	60.000 h

DIMENSIONED DRAWING



DIMMER COMPATIBILITY

Compatible trailing edge dimmer

Kompatible Phasenabschnittdimmer

Manufacturer Hersteller	Model Model	Q'ty of parallel connection Anzahl der Parallelschaltungen
PHILIPS	SED-200A	16
Schneider Electric	SBD315RC	8
Etman	ETM329	8
Etman	ETM327	13

NOTE

In the case of series-produced items, the dimensions, weights and designs specified in catalogs etc. are subject to standard commercial and reasonable tolerances of series production. These deviations do not constitute a defect. Even minor deviations in size, color and surface as well as technical modifications shall not be considered a defect. Warranted properties shall only apply if they have been confirmed by us in writing.

The guarantee period for the product is 3 years and begins on the day of shipment. Reference is the date of the delivery bill. The guarantee period may differ for accessories.