

# Marzana S - LED spotlight 55 mm

230 V AC - stainless steel shield - IP66

- dimmable, high-quality LED spotlight for outdoor use
- robust housing made of aluminum, powder-coated gray
- color temperature: 3000 K, others on request with MOQ 100 pieces
- standard narrow and wide beam; other beam angles on request with MOQ 100 pieces
- easy installation by direct connection to 230 V AC on dimmable power supply unit
- including 2 m connection cable: 3 pole
- 120° pivotable and 360° rotatable
- protection class IP 66: complete protection against contact and dust; protection against strong water jet from any direction



## LIGHT DATA

|                                  | 62023021 | 62023038 |
|----------------------------------|----------|----------|
| Typ. color temperature           |          | 3000 K   |
| Light color                      |          | white    |
| LED beam angle                   | 16 °     | 44 °     |
| Typ. luminous flux               | 375 lm   | 340 lm   |
| Efficiency                       | 45 lm/W  | 40 lm/W  |
| EEC of installed light source(s) |          | G        |
| Typ. color rendering index       |          | 90       |
| SDCM MacAdam                     |          | 3        |


## POWER DATA

|                     | 62023021 | 62023038 |
|---------------------|----------|----------|
| Operating voltage   |          | 230 V AC |
| Current consumption |          | 37 mA    |
| Typ. power          |          | 8,4 W    |

## FURTHER DATA

|                             | 62023021 | 62023038                           |
|-----------------------------|----------|------------------------------------|
| Length                      |          | 118 mm                             |
| Height                      |          | 93 mm                              |
| Diameter                    |          | 55 mm                              |
| Type of protection          |          | IP 66                              |
| Indoor/Outdoor              |          | Outdoor                            |
| Material                    |          | aluminium                          |
| Finish                      |          | powder-coated                      |
| Colour                      |          | anthrazitgrau RAL7016              |
| Cable termination           |          | 2m cable with free wire ends       |
| Max. temperature Tc         |          | 85 ° C                             |
| Max. ambient temperature Ta |          | -20 ° C ~ +40 ° C                  |
| Lifetime L90                |          | 60.000 h                           |
| Remarks                     |          | Verbindungsschrauben aus Edelstahl |

## DIMENSIONED DRAWING



## ACCESSORIES

| 62023001    |                                  |
|-------------|----------------------------------|
| Description | Marzana S Erdspieß Ø 38 x 170 mm |

## DIMMER COMPATIBILITY

| Hersteller / Manufacturer | Modell / Model | Anzahl paralleler Verbindungen<br>Quantity of parallel connections |
|---------------------------|----------------|--|
| ABB                       | 6519 U         | 15   |
| ABB                       | 6526 U         | 13   |
| JUNG                      | 1224 LED UDE   | 14   |
| Berker                    | 2861           | 10   |
| JUNG                      | 254 UDIE 1     | 10   |
| JUNG                      | 225 TDE        | 14   |
| EGANT                     | U321V2         | 15   |
| Schneider                 | SBD200LED      | 13   |
| Schneider                 | SBD315RC       | 14   |
| Merten                    | SBD200LED      | 13   |
| Berker                    | 2874           | 12   |
| Eetako                    | EUD61NPL-230V  | 12   |

## NOTE

In the case of series-produced items, the dimensions, weights and designs specified in catalogs etc. are subject to standard commercial and reasonable tolerances of series production. These deviations do not constitute a defect. Even minor deviations in size, color and surface as well as technical modifications shall not be considered a defect. Warranted properties shall only apply if they have been confirmed by us in writing.

The guarantee period for the product is 3 years and begins on the day of shipment. Reference is the date of the delivery bill. The guarantee period may differ for accessories.