

Marzana M - LED spotlight 82 mm

230 V AC - stainless steel shield - IP66

- dimmable, high-quality LED spotlight for outdoor use
- robust housing made of aluminum, powder-coated gray
- color temperature: 3000 K, others on request with MOQ 100 pieces
- standard narrow and wide beam; other beam angles on request with MOQ 100 pieces
- easy installation by direct connection to 230 V AC on dimmable power supply unit
- including 2 m connection cable: 3 pole
- 120° pivotable and 360° rotatable
- protection class IP 66: complete protection against contact and dust; protection against strong water jet from any direction



LIGHT DATA

	62033018	62033055
Typ. color temperature		3000 K
Light color		white
LED beam angle	15 °	46 °
Typ. luminous flux	1315 lm	1050 lm
Efficiency	93 lm/W	74 lm/W
EEC of installed light source(s)		E
Typ. color rendering index		90
SDCM MacAdam		3


POWER DATA

	62033018	62033055
Operating voltage		230 V AC
Current consumption		62 mA
Typ. power		14,2 W

FURTHER DATA

	62033018	62033055
Length		148 mm
Height		126 mm
Diameter		82 mm
Type of protection		IP 66
Indoor/Outdoor		Outdoor
Material		aluminium
Finish		powder-coated
Colour		anthrazitgrau RAL7016
Cable termination		2m cable with free wire ends
Max. temperature Tc		85 ° C
Max. ambient temperature Ta		-20 ° C ~ +40 ° C
Lifetime L90		60.000 h
Remarks		Verbindungsschrauben aus Edelstahl

DIMENSIONED DRAWING



ACCESSORIES

62033001	
Description	Marzana M Erdspieß ϕ 65 x 225 mm

DIMMER COMPATIBILITY

Hersteller / Manufacturer	Modell / Model	Anzahl paralleler Verbindungen Quantity of parallel connections
ABB	6519 U	15
ABB	6526 U	13
JUNG	1224 LED UDE	14
Berker	2861	10
JUNG	254 UDIE 1	10
JUNG	225 TDE	14
EGANT	U321V2	15
Schneider	SBD200LED	13
Schneider	SBD315RC	14
Merten	SBD200LED	13
Berker	2874	12

NOTE

In the case of series-produced items, the dimensions, weights and designs specified in catalogs etc. are subject to standard commercial and reasonable tolerances of series production. These deviations do not constitute a defect. Even minor deviations in size, color and surface as well as technical modifications shall not be considered a defect. Warranted properties shall only apply if they have been confirmed by us in writing.

The guarantee period for the product is 3 years and begins on the day of shipment. Reference is the date of the delivery bill. The guarantee period may differ for accessories.