

# Scotto S - recessed LED luminaire 50 mm

24 V DC - stainless steel shield - IP67

- high-quality LED recessed luminaire for outdoor use
- robust aluminum luminaire with SUS 316 stainless steel shield
- for accent lighting or as positioning light in garden and lands-cape applications
- color temperature: 3000 K, other color temperatures on re-quest (MOQ 100 pieces)
- narrow and wide beam as standard; other beam angles with MOQ 100 pieces
- IP 67 protection: complete protection against contact and dust; protection against submersion up to 30 minutes
- impact resistance level IK08 with 1,000 kg load capacity



## LIGHT DATA

	62043016	62043031
Typ. color temperature		3000 K
Light color		white
LED beam angle	16 °	38 °
Typ. luminous flux	185 lm	180 lm
Efficiency	35 lm/W	34 lm/W
EEC of installed light source(s)		G
Typ. color rendering index		90
SDCM MacAdam		3

## POWER DATA

	62043016	62043031
Operating voltage		24 V DC
Current consumption		220 mA
Typ. power		5,3 W

## FURTHER DATA

	62043016	62043031
Height		61 mm
Diameter		50 mm
Type of protection		IP 67
Indoor/Outdoor		Outdoor
Material		Aluminium
Material shield		stainless steel
Max. temperature Tc		85 ° C
Max. ambient temperature Ta		-20 ° C ~ +40 ° C
Lifetime L90		60.000 h

## DIMENSIONED DRAWING



## NOTE

In the case of series-produced items, the dimensions, weights and designs specified in catalogs etc. are subject to standard commercial and reasonable tolerances of series production. These deviations do not constitute a defect. Even minor deviations in size, color and surface as well as technical modifications shall not be considered a defect. Warranted properties shall only apply if they have been confirmed by us in writing.

The guarantee period for the product is 3 years and begins on the day of shipment. Reference is the date of the delivery bill. The guarantee period may differ for accessories.