

Scotto M - recessed LED luminaire 77 mm

230 V AC - stainless steel shield - IP67

- high-quality LED recessed luminaire for outdoor use
- robust aluminum luminaire with SUS 316 stainless steel shield
- for accent lighting or as positioning light in garden and lands-cape applications
- color temperature: 3000 K, other color temperatures on re-quest (MOQ 100 pieces)
- narrow and wide beam as standard; other beam angles with MOQ 100 pieces
- IP 67 protection: complete protection against contact and dust; protection against submersion up to 30 minutes
- impact resistance level IK08 with 1,000 kg load capacity



LIGHT DATA

	62053016	62053037
Typ. color temperature	3000 K	
Light color	white	
LED beam angle	16 °	37 °
Typ. luminous flux	335 lm	355 lm
Efficiency	58 lm/W	61 lm/W
EEC of installed light source(s)	E	
Typ. color rendering index	90	
SDCM MacAdam	3	

POWER DATA

	62053016	62053037
Operating voltage	230 V AC	
Current consumption	25 mA	
Typ. power	5,8 W	

FURTHER DATA

	62053016	62053037
Height	91 mm	
Diameter	77 mm	
Type of protection	IP 67	
Indoor/Outdoor	Outdoor	
Material	Aluminium	
Material shield	stainless steel	
Max. temperature Tc	85 ° C	
Max. ambient temperature Ta	-20 °C ~ +40 ° C	
Lifetime L90	60.000 h	

DIMENSIONED DRAWING



NOTE

In the case of series-produced items, the dimensions, weights and designs specified in catalogs etc. are subject to standard commercial and reasonable tolerances of series production. These deviations do not constitute a defect. Even minor deviations in size, color and surface as well as technical modifications shall not be considered a defect. Warranted properties shall only apply if they have been confirmed by us in writing.

The guarantee period for the product is 3 years and begins on the day of shipment. Reference is the date of the delivery bill. The guarantee period may differ for accessories.