

Merano Sauna linear luminaire

Luminaire made of anodised aluminium - light colour warm white - individual length up to max. 505 mm - opal diffuser - indoor

- linear luminaire for indirect lighting - for ceiling and wall mounting in dry saunas and operation in a maximum ambient temperature of 100 °C
- individual lengths from 85 to 505 mm, incl. end caps
- various brackets enable individual mounting solutions and alignment of the light
- available in warm white 2700 K, with opal diffuser
- alignment of several luminaires in a line with connectors incl. 5 m teflon cable with free wire ends
- estimated lifetime L70 at Ta < 110 °C > 60,000 h



LIGHT DATA

Typ. color temperature
Color index
Lichtstrom bei max. Baulänge (505 mm)
Light color
LED beam angle
Typ. luminous flux
Dominating wavelength
Efficiency
Energy efficiency class
Typ. color rendering index
SDCM MacAdam
Number of LEDs

POWER DATA

	62379001
Constant voltage/Constant current	CV
Operating voltage	24 V DC
Typ. current consumption	120 mA

FURTHER DATA

	62379001
Color of material	aluminium eloxiert
Type of protection	IP 40
Indoor/Outdoor	Indoor
Umgebungstemperatur Ta max	100 ° C
Width	18,4 mm

	62379001
Height	20,8 mm
Cable length/cable finishing	5m cable with free wire ends
Remarks	Anschlußkabel aus Teflon

ACCESSORIES

	50990090	50990091	50990190	50990191	50990291
Description	2x mounting clips, incl. screws, suitable for profiles of the BARdolino family	2x mounting clips 45°, incl. screws, suitable for profiles of the BARdolino family	mounting clip set, incl. 2 holding clips + 2 screws, high holding force, suitable for profiles of the BARdolino family	2x mounting clips pivoted, incl. screws, suitable for profiles of the BARdolino family	1x metal connector, suitable for profiles of the BARdolino family
Material	304 stainless steel				
Length	12 mm		14 mm	18,8 mm	60 mm
Width	19,3 mm	15,4 mm	20,81 mm	32,3 mm	19,5 mm
Height	8 mm	18,6 mm	9,1 mm	22,4 mm	6,2 mm



TECHNICAL DRAWING

The guarantee period for the product is 5 years and begins on the day of shipment.

Reference is the date of the delivery bill. The guarantee period may differ for accessories.