

# TRIESTE surface-mounted downlight CC

- dimmable downlight series, consisting of surface-mounted luminaires
- puristic design in matt signal white in round form
- ideal for interior illumination in hotels, restaurants, bars or public buildings
- numerous configuration options for individual requirements



## LIGHT DATA

	62407515	62407526	62407527	62407533	62407615	62407626	62407627	62407633
<b>Color of body</b>	weiß							
<b>Typ. color temperature</b>	5700 K	4000 K	2700 K	3000 K	5700 K	4000 K	2700 K	3000 K
<b>Light color</b>	daylight	cold white	warm white	white	daylight	cold white	warm white	white
<b>Typ. luminous flux</b>	900 lm~1215 lm		840 lm~1134 lm		900 lm~1215 lm		840 lm~1134 lm	
<b>Efficiency</b>	110 lm/W		103 lm/W		110 lm/W		103 lm/W	
<b>Energy efficiency class</b>	A+							
<b>Typ. color rendering index</b>	83							
<b>SDCM MacAdam</b>	3							
<b>Beam angle</b>	15 °				24 °			
<b>Remarks</b>	dimmable							
	62407715	62407726	62407727	62407733	62407815	62407826	62407827	62407833
<b>Color of body</b>	weiß							
<b>Typ. color temperature</b>	5700 K	4000 K	2700 K	3000 K	5700 K	4000 K	2700 K	3000 K
<b>Light color</b>	daylight	cold white	warm white	white	daylight	cold white	warm white	white
<b>Typ. luminous flux</b>	900 lm~1215 lm		840 lm~1134 lm		900 lm~1215 lm		840 lm~1134 lm	
<b>Efficiency</b>	110 lm/W		103 lm/W		110 lm/W		103 lm/W	
<b>Energy efficiency class</b>	A+							
<b>Typ. color rendering index</b>	83							
<b>SDCM MacAdam</b>	3							
<b>Beam angle</b>	38 °				60 °			
<b>Remarks</b>	dimmable							


## POWER DATA

	62407515	62407526	62407527	62407533	62407615	62407626	62407627	62407633
<b>Constant current range</b>	350 mA~600 mA							
<b>Typ. power</b>	11 W							
<b>LED type</b>	CREE CXA 1507							
	62407715	62407726	62407727	62407733	62407815	62407826	62407827	62407833
<b>Constant current range</b>	350 mA~600 mA							
<b>Typ. power</b>	11 W							
<b>LED type</b>	CREE CXA 1507							

## FURTHER DATA

	62407515	62407526	62407527	62407533	62407615	62407626	62407627	62407633
Height	95 mm							
Diameter	80 mm							
Type of protection	IP 40							
Cable length	300 mm							
Connection	Connector							
Max. temperature Tc	75 ° C							
Max. ambient temperature Ta	40 ° C							
	62407715	62407726	62407727	62407733	62407815	62407826	62407827	62407833
Height	95 mm							
Diameter	80 mm							
Type of protection	IP 40							
Cable length	300 mm							
Connection	Connector							
Max. temperature Tc	75 ° C							
Max. ambient temperature Ta	40 ° C							

## DIMENSIONED DRAWING



The guarantee period for the product is 3 years and begins on the day of shipment.

Reference is the date of the delivery bill. The guarantee period may differ for accessories.