

TRIESTE surface-mounted downlight CV

- dimmable downlight series, consisting of surface-mounted luminaires
- puristic design in matt signal white in round form
- ideal for interior illumination in hotels, restaurants, bars or public buildings
- CV version: easily combinable with LED strips in a lighting system by using the same power supply
- also available as CC version on request



LIGHT DATA

	62408115	62408126	62408127	62408133	62408215	62408226	62408227	62408233
Color of body	weiß							
Typ. color temperature	5700 K	4000 K	2700 K	3000 K	5700 K	4000 K	2700 K	3000 K
Light color	daylight	cold white	warm white	white	daylight	cold white	warm white	white
Typ. luminous flux	1215 lm		1134 lm		1215 lm		1134 lm	
Efficiency	97 lm/W		90 lm/W		97 lm/W		90 lm/W	
Energy efficiency class	A+							
Typ. color rendering index	83							
SDCM MacAdam	3							
Beam angle	15 °				24 °			
Remarks	dimmable							
	62408315	62408326	62408327	62408333	62408415	62408426	62408427	62408433
Color of body	weiß							
Typ. color temperature	5700 K	4000 K	2700 K	3000 K	5700 K	4000 K	2700 K	3000 K
Light color	daylight	cold white	warm white	white	daylight	cold white	warm white	white
Typ. luminous flux	1215 lm		1134 lm		1215 lm		1134 lm	
Efficiency	97 lm/W		90 lm/W		97 lm/W		90 lm/W	
Energy efficiency class	A+							
Typ. color rendering index	83							
SDCM MacAdam	3							
Beam angle	38 °				60 °			
Remarks	dimmable							


POWER DATA

	62408115	62408126	62408127	62408133	62408215	62408226	62408227	62408233
Operating voltage DC	24 V DC							
Typ. power	12,5 W							
LED type	CREE CXA 1507							
	62408315	62408326	62408327	62408333	62408415	62408426	62408427	62408433
Operating voltage DC	24 V DC							
Typ. power	12,5 W							
LED type	CREE CXA 1507							

FURTHER DATA

	62408115	62408126	62408127	62408133	62408215	62408226	62408227	62408233
Length	80 mm							
Width	80 mm							
Height	95 mm							
Type of protection	IP 40							
Cable length	300 mm							
Connection	free wire ends							
Max. temperature Tc	75 ° C							
Max. ambient temperature Ta	40 ° C							
	62408315	62408326	62408327	62408333	62408415	62408426	62408427	62408433
Length	80 mm							
Width	80 mm							
Height	95 mm							
Type of protection	IP 40							
Cable length	300 mm							
Connection	free wire ends							
Max. temperature Tc	75 ° C							
Max. ambient temperature Ta	40 ° C							

DIMENSIONED DRAWING



The guarantee period for the product is 3 years and begins on the day of shipment.

Reference is the date of the delivery bill. The guarantee period may differ for accessories.