

# MILANO UGR - Pendelleuchte 1126 mm

- versatile pendant luminaire with low glare and high quality design.
- UGR <16 at intensive 3,580 lm/m for demanding screen workstations
- elegant black powder-coated pendant luminaire (RAL 9005 fine structure) made of aluminum therefore also for retail and general lighting applications
- easy connection to 230 V (integrated dimmable Tridonic DALI power supply)
- HCL ready thanks to Tunable White 2700 - 6500 K light source
- color temperature 4000 K standard, other color temperatures on request
- estimated lifetime L80/B10 at Ta < 55 °C >: > 60,000 h



## LIGHT DATA

	62616230	62616240
Typ. color temperature	2700 K-6500 K	4000 K
Light color	tunable white	cold white
Typ. luminous flux	3588 lm-4027 lm	3593 lm
Efficiency	76 lm/W-86 lm/W	76 lm/W
EEC of installed light source(s)		F
Typ. color rendering index	86	85

## POWER DATA

	62616230	62616240
Operating voltage		230 V AC
Current consumption		200 mA
Typ. power		47 W

## FURTHER DATA

	62616230	62616240
Type of protection		IP 40
Indoor/Outdoor		Indoor
Umgebungstemperatur Ta max		55 ° C
Length		1126 mm
Width		44 mm
Height		68 mm
Remarks	UGR <16 (Unified Glare Rating / vereinheitlichte Blendungsbewertung) integriertes dimmbares Tridonic DALI Netzteil	

## DIMENSIONED DRAWING



## NOTE

In the case of series-produced items, the dimensions, weights and designs specified in catalogs etc. are subject to standard commercial and reasonable tolerances of series production. These deviations do not constitute a defect. Even minor deviations in size, color and surface as well as technical modifications shall not be considered a defect. Warranted properties shall only apply if they have been confirmed by us in writing.

The guarantee period for the product is 5 years and begins on the day of shipment. Reference is the date of the delivery bill. The guarantee period may differ for accessories.