

Como Midi Outdoor Accent Luminaire

- dimmable, high quality LED spot for indoor and outdoor applications
- IP 67 protection due to high-end encapsulation
- traversible, loadable up to 500kg, ideal for pavements
- available with anodised aluminium shield or stainless steel shields with various surface finishings
- estimated lifetime L70 at Ta < 45 °C: > 60,000 h
- incl. 5 m connection cable with free wire ends



Please observe the installation and safety instructions at <https://www.barthelme.de/content/en/manuals.aspx> !



LIGHT DATA

	62792801	62792802	62792803	62793301	62793302	62793303	62792601	62792602	62792603	62791501	62791502	62791503
Typ. color temperature	2700 K			3000 K			4200 K			5700 K		
Light color	warm white			white			cold white			daylight		
Typ. luminous flux	19 lm			20 lm			22 lm			23 lm		
Efficiency	38 lm/W			40 lm/W			44 lm/W			46 lm/W		
Energy efficiency class	A++											
Typ. color rendering index	85											

POWER DATA

	62791501	62791502	62791503	62792601	62792602	62792603	62792801	62792802	62792803	62793301	62793302	62793303
Operating voltage	24 V DC											
Typ. power	0,5 W											

FURTHER DATA

	62791501	62792601	62792801	62793301
Height	18,3 mm			
Mounting diameter	42 mm			
Max. temperature Tc	64 ° C			
Lifetime L70	>60.000 h			
Load capacity	500 kg			
Material shield	Anodised aluminium			
	62791502	62792602	62792802	62793302
Material shield	316L stainless steel, brushed			
	62791503	62792603	62792803	62793303
Material shield	316L stainless steel, high gloss polish			