

Pisa 1.2 Einbauleuchte Haltefeder RGB / RGBW

Blende Edelstahl V2A / V4A gebürstet

- dimmbare, hochwertige LED-Leuchte
- gefrästes Gehäuse aus Aluminium, eloxiert
- Blende Edelstahl V2A oder V4A gebürstet
- mit Haltefedern für den Einbau in Holzböden und -wänden
- 25° Abstrahlwinkel
- mit integrierter Membran zur Vermeidung von Betauung und Verschmutzung durch Druckausgleich



Please observe the installation and safety instructions at <https://www.barthelme.de/content/en/manuals.aspx> !



LIGHT DATA

	627331253	627336253	627431253	627436253
Material shield	304 stainless steel		316L stainless steel, brushed	
Light color	RGB	RGBW	RGB	RGBW
Typ. luminous flux	145 lm	225 lm	145 lm	225 lm
Efficiency	48 lm/W	55 lm/W	48 lm/W	55 lm/W
Energy efficiency class	A+			
Beam angle	25 °			


POWER DATA

	627331253	627336253	627431253	627436253
Operating voltage				
Operating voltage				
Constant current	3x350 mA	4x350 mA	3x350 mA	4x350 mA
Typ. power	3 W	4,1 W	3 W	4,1 W

FURTHER DATA

	627331253	627336253	627431253	627436253
Height	66,5 mm			
Mounting diameter	40 mm			
Diameter	54,5 mm			
Type of protection	IP 67			
Material	Aluminium			
Cable termination	5m cable with free wire ends			
Lifetime estimation	>60.000 h			

DIMENSIONED DRAWING



NOTE

In the case of series-produced items, the dimensions, weights and designs specified in catalogs etc. are subject to standard commercial and reasonable tolerances of series production. These deviations do not constitute a defect. Even minor deviations in size, color and surface as well as technical modifications shall not be considered a defect. Warranted properties shall only apply if they have been confirmed by us in writing.

The guarantee period for the product is 3 years and begins on the day of shipment.

Reference is the date of the delivery bill. The guarantee period may differ for accessories.