

# PRATO

## LED insert for handrails

- flush installation in handrails, tubes etc.
- dust-proof encapsulation
- resistant against weather- and UV-radiation
- straightforward and secure assembly with springs or screws
- very little heat generation and low energy consumption
- typ. power: 0.5 W
- incl. 20 cm cable/connector per side



### LIGHT DATA

	67600413	67601413	67600428	67601428	67600426	67601426
<b>Variety</b>	with mounting bracket	vandal-proof screw connection	with mounting bracket	vandal-proof screw connection	with mounting bracket	vandal-proof screw connection
<b>Typ. color temperature</b>			3300 K		4500 K	
<b>Typ. wavelength</b>	470 nm					
<b>Light color</b>	blue		warm white		cold white	
<b>Efficiency</b>	92 lm/W					
<b>Energy efficiency class</b>	A			A++		
<b>Typ. color rendering index</b>				80		
<b>LED beam angle</b>	120 °					
<b>Lifetime L70</b>	>30.000 h					

### POWER DATA

	67600413	67601413	67600428	67601428	67600426	67601426
<b>Operating voltage</b>	24 V DC					
<b>Typ. power</b>	0,5 W					
<b>Typ. luminous flux</b>	8 lm		46 lm			
<b>Lifetime L70</b>	>30.000 h					

### FURTHER DATA

	67600413	67601413	67600428	67601428	67600426	67601426
<b>Max. temperature Tc</b>	65 ° C					
<b>Length</b>	74 mm					
<b>Width</b>	10 mm					
<b>Height</b>	24 mm					
<b>Remark</b>	with mounting bracket	vandal-proof screw connection	with mounting bracket	vandal-proof screw connection	with mounting bracket	vandal-proof screw connection

**DIMENSIONED DRAWING**

