

# Verona R MIDI outdoor spot

## with honeycomb mesh (glare suppression)

- dimmable, high quality LED spot for outdoor applications
- milled aluminium housing, anodised black
- with integrated membrane for prevention of condensation and contamination through pressure compensation
- low voltage drop due to 48 V DC operation enables longer cable routings
- fitted with high quality power LEDs from OSRAM
- with honeycomb mesh for lateral glare suppression
- incl. 5 m connection cable with angled M8 socket and free wire ends



Please observe the installation and safety instructions at <https://www.barthelme.de/content/en/manuals.aspx> !



### LIGHT DATA

	692128101	692128201	692128351
Typ. color temperature		2700 K	
Light color		warm white	
Typ. luminous flux		1050 lm	
Efficiency		70 lm/W	
Energy efficiency class		A	
Typ. color rendering index		82	
Beam angle	10 °	20 °	35 °

	692133101	692133201	692133351
Typ. color temperature		3000 K	
Light color		white	
Typ. luminous flux		1136 lm	
Efficiency		76 lm/W	
Energy efficiency class		A	
Typ. color rendering index		82	
Beam angle	10 °	20 °	35 °

	692126101	692126201	692126351
Typ. color temperature		4000 K	
Light color		cold white	
Typ. luminous flux		1136 lm	
Efficiency		76 lm/W	
Energy efficiency class		A	
Typ. color rendering index		82	
Beam angle	10 °	20 °	35 °

## POWER DATA

	692126101	692126201	692126351	692128101	692128201	692128351	692133101	692133201	692133351
Operating voltage	48 V DC								
Operating voltage									
Current consumption	312,5 mA								
Typ. power	15 W								

## FURTHER DATA

	692126101	692126201	692126351	692128101	692128201	692128351	692133101	692133201	692133351
Length	95 mm								
Height	127 mm								
Diameter	80 mm								
Type of protection	IP 67								
Material	Aluminium								
Cable termination	5m cable with free wire ends								
Lifetime estimation	>36.000 h								
Remarks	with Honeycomb Mesh (anti-glare insert), 48 V operation for longer cable runs, incl. adjustable retaining clip, with integrated membrane to prevent condensation, M8 screw connection for cable connection								

## ACCESSORIES

	62700051
Description	ground spike, 304 stainless steel, incl. screws for attaching the luminaire to the ground spike
Material	304 stainless steel
Length	42 mm
Width	42 mm
Height	203 mm



## NOTE

In the case of series-produced items, the dimensions, weights and designs specified in catalogs etc. are subject to standard commercial and reasonable tolerances of series production. These deviations do not constitute a defect. Even minor deviations in size, color and surface as well as technical modifications shall not be considered a defect. Warranted properties shall only apply if they have been confirmed by us in writing.

The guarantee period for the product is 3 years and begins on the day of shipment.

Reference is the date of the delivery bill. The guarantee period may differ for accessories.