




# BERgamo HP

Linear Luminaire - anodised aluminium - Light colour white -  
Length 336mm - Indoor

- elegant wallwasher with high lumen output for indoor and outdoor architectural area illumination
- seamless and shadowless alignment possible, several luminaires operable with one controller
- Impact resistance: IK10
- Temperature monitoring. Automatic dimming of the LEDs in the case of overheating to protect from damage
- anodised aluminium housing, coloured eloxal on request
- indoor: optionally with a straight plastic cover – with or without glare shield - or with a half-round cover for special protection against dust and dirt



## LATERAL VIEW OF THE THREE VARIETIES



## LIGHT DATA

	62332617	62332626	62332637	62332655	62332817	62332826	62332837	62332855	62333317	62333326	62333337	62333355
<b>dimmable</b>	dimmable											
	63332617	63332626	63332637	63332655	63332817	63332826	63332837	63332855	63333317	63333326	63333337	63333355
	64332617	64332626	64332637	64332655	64332817	64332826	64332837	64332855	64333317	64333326	64333337	64333355
<b>Typ. color temperature</b>	4000 K				2700 K				3000 K			
<b>Light color</b>	cold white				warm white				white			
<b>LED beam angle</b>	17 °	26 °	37 °	43x16 °	17 °	26 °	37 °	43x16 °	17 °	26 °	37 °	43x16 °
<b>Typ. luminous flux</b>	1980 lm				1780 lm				1880 lm			
<b>Efficiency</b>	110 lm/W				99 lm/W				104 lm/W			
<b>Energy efficiency class</b>	A+											
<b>Typ. color rendering index</b>	83											
<b>SDCM MacAdam</b>	3											
<b>Number of LEDs</b>	12											

## POWER DATA

	64332617	64332626	64332637	64332655	64332817	64332826	64332837	64332855	64333317	64333326	64333337	64333355
Constant voltage/Constant current	CV											
Operating voltage	24 V DC											
Typ. current consumption	750 mA											
Typ. power	18 W											
Lifetime L70	>36000 h											

## FURTHER DATA

	64332617	64332626	64332637	64332655	64332817	64332826	64332837	64332855	64333317	64333326	64333337	64333355
Material	Aluminium											
Finish	anodised											
Color of material	aluminium eloxiert											
Type of protection	IP 30											
Indoor/Outdoor	Indoor											
Umgebungstemperatur Ta max	55 ° C											
Length	336 mm											
Width	28 mm											
Height	39 mm											
Weight	350 gr											
Cable length/cable finishing	5m cable with free wire ends											
Remarks	Stoßfestigkeitsgrad: IK10 ohne Haltebügel und Ausleger											

Maximum values at Ta=25°C

## ACCESSORIES

	62399487	62399488	62399489
Description	mounting bracket standard, for mounting in ceiling and floor, incl. 2 screws and 2 dowels, distance to wall 15 mm	cantilever arm, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 65 mm	cantilever arm long, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 201 mm
Material	304 stainless steel		
Length	73,7 mm	71,4 mm	206,3 mm
Width	58 mm		
Height	20,4 mm	55,5 mm	85,5 mm
Remarks	Mounting bracket V2A steel, nylon dowel, spacer sleeve brass nickel plated, screws, washers, snorkel washer, nut		



The guarantee period for the product is 5 years and begins on the day of shipment.

Reference is the date of the delivery bill. The guarantee period may differ for accessories.