




# BERgamo HP

## Linear Luminaire - anodised aluminium - RGBW - Length 666mm - Indoor

- elegant wallwasher with high lumen output for indoor and outdoor architectural area illumination
- seamless and shadowless alignment possible, several luminaires operable with one controller
- Impact resistance: IK10
- Temperature monitoring. Automatic dimming of the LEDs in the case of overheating to protect from damage
- anodised aluminium housing, coloured eloxal on request
- indoor: optionally with a straight plastic cover – with or without glare shield - or with a half-round cover for special protection against dust and dirt



### LATERAL VIEW OF THE THREE VARIETIES



### LIGHT DATA

|                         | 62663617 | 62663626 | 62663637 | 62663655 | 63663617 | 63663626 | 63663637 | 63663655 | 64663617 | 64663626 | 64663637 | 64663655 |
|-------------------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| Light color             | RGBW     |          |          |          |          |          |          |          |          |          |          |          |
| LED beam angle          | 17 °     | 26 °     | 37 °     | 43x16 °  | 17 °     | 26 °     | 37 °     | 43x16 °  | 17 °     | 26 °     | 37 °     | 43x16 °  |
| Typ. luminous flux      | 3100 lm  |          |          |          |          |          |          |          |          |          |          |          |
| Efficiency              | 53 lm/W  |          |          |          |          |          |          |          |          |          |          |          |
| Energy efficiency class | B        |          |          |          |          |          |          |          |          |          |          |          |
| Number of LEDs          | 24       |          |          |          |          |          |          |          |          |          |          |          |

## POWER DATA

|                                   | 62663617 | 62663626 | 62663637 | 62663655 | 63663617 | 63663626 | 63663637 | 63663655 | 64663617 | 64663626 | 64663637 | 64663655 |
|-----------------------------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| Constant voltage/Constant current | CC       |          |          |          |          |          |          |          |          |          |          |          |
| Operating current                 | 4x700 mA |          |          |          |          |          |          |          |          |          |          |          |
| Typ. power                        | 59 W     |          |          |          |          |          |          |          |          |          |          |          |
| Lifetime L70                      | >36000 h |          |          |          |          |          |          |          |          |          |          |          |

## FURTHER DATA

|                              | 62663617   | 62663626 | 62663637 | 62663655 | 63663617 | 63663626 | 63663637 | 63663655 | 64663617 | 64663626 | 64663637 | 64663655 |
|------------------------------|--|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| Material                     | Aluminium  |          |          |          |          |          |          |          |          |          |          |          |
| Finish                       | anodised   |          |          |          |          |          |          |          |          |          |          |          |
| Color of material            | aluminium eloxiert   |          |          |          |          |          |          |          |          |          |          |          |
| Type of protection           | IP 30  |          |          |          |          |          |          |          |          |          |          |          |
| Indoor/Outdoor               | Indoor   |          |          |          |          |          |          |          |          |          |          |          |
| Umgebungstemperatur Ta max   | 55 ° C   |          |          |          |          |          |          |          |          |          |          |          |
| Length                       | 666 mm   |          |          |          |          |          |          |          |          |          |          |          |
| Width                        | 28 mm  |          |          |          |          |          |          |          |          |          |          |          |
| Height                       | 39 mm  |          |          | 54 mm    |          |          | 39 mm    |          |          |          |          |          |
| Weight                       | 700 gr   |          |          | 780 gr   |          |          | 700 gr   |          |          |          |          |          |
| Cable length/cable finishing | 5m cable with free wire ends   |          |          |          |          |          |          |          |          |          |          |          |
| Remarks                      | Impact resistance: IK10<br>without mounting bracket and cantilever arm |          |          |          |          |          |          |          |          |          |          |          |

Maximum values at Ta=25°C

## ACCESSORIES

|             | 62399487  | 62399488   | 62399489   |
|-------------|---|--|--|
| Description | mounting bracket standard, for mounting in ceiling and floor, incl. 2 screws and 2 dowels, distance to wall 15 mm | cantilever arm, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 65 mm | cantilever arm long, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 201 mm |
| Material    | 304 stainless steel   |  |  |
| Length      | 73,7 mm   | 71,4 mm  | 206,3 mm   |
| Width       | 58 mm   |  |  |
| Height      | 20,4 mm   | 55,5 mm  | 85,5 mm  |
| Remarks     | Mounting bracket V2A steel, nylon dowel, spacer sleeve brass nickel plated, screws, washers, snorkel washer, nut  |  |  |



The guarantee period for the product is 5 years and begins on the day of shipment.

Reference is the date of the delivery bill. The guarantee period may differ for accessories.