




# BERgamo HP

Linear Luminaire - anodised aluminium - Light colour white -  
 Length 666mm - Indoor

- elegant wallwasher with high lumen output for indoor and outdoor architectural area illumination
- seamless and shadowless alignment possible, several luminaires operable with one controller
- Impact resistance: IK10
- Temperature monitoring. Automatic dimming of the LEDs in the case of overheating to protect from damage
- anodised aluminium housing, coloured eloxal on request
- indoor: optionally with a straight plastic cover – with or without glare shield - or with a half-round cover for special protection against dust and dirt



## LATERAL VIEW OF THE THREE VARIETIES



## LIGHT DATA

	62662617	62662626	62662637	62662655	62662817	62662826	62662837	62662855	62663317	62663326	62663337	62663355
<b>dimmable</b>	dimmable											
	63662617	63662626	63662637	63662655	63662817	63662826	63662837	63662855	63663317	63663326	63663337	63663355
	64662617	64662626	64662637	64662655	64662817	64662826	64662837	64662855	64663317	64663326	64663337	64663355
<b>Typ. color temperature</b>	4000 K				2700 K				3000 K			
<b>Light color</b>	cold white				warm white				white			
<b>LED beam angle</b>	17 °	26 °	37 °	43x16 °	17 °	26 °	37 °	43x16 °	17 °	26 °	37 °	43x16 °
<b>Typ. luminous flux</b>	3960 lm				3560 lm				3760 lm			
<b>Efficiency</b>	110 lm/W				99 lm/W				104 lm/W			
<b>Energy efficiency class</b>	A+											
<b>Typ. color rendering index</b>	83											
<b>SDCM MacAdam</b>	3											
<b>Number of LEDs</b>	24											

## POWER DATA

	64662617	64662626	64662637	64662655	64662817	64662826	64662837	64662855	64663317	64663326	64663337	64663355
Constant voltage/Constant current	CV											
Operating voltage	24 V DC											
Typ. power	36 W											
Lifetime L70	>36000 h											

## FURTHER DATA

	64662617	64662626	64662637	64662655	64662817	64662826	64662837	64662855	64663317	64663326	64663337	64663355
Material	Aluminium											
Finish	anodised											
Color of material	aluminium eloxiert											
Type of protection	IP 30											
Indoor/Outdoor	Indoor											
Umgebungstemperatur Ta max	55 ° C											
Length	666 mm											
Width	28 mm											
Height	39 mm											
Weight	700 gr											
Cable length/cable finishing	5m cable with free wire ends											
Remarks	Impact resistance: IK10 without mounting bracket and cantilever arm											

Maximum values at Ta=25°C

## ACCESSORIES

	62399487	62399488	62399489
Description	mounting bracket standard, for mounting in ceiling and floor, incl. 2 screws and 2 dowels, distance to wall 15 mm	cantilever arm, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 65 mm	cantilever arm long, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 201 mm
Material	304 stainless steel		
Length	73,7 mm	71,4 mm	206,3 mm
Width	58 mm		
Height	20,4 mm	55,5 mm	85,5 mm
Remarks	Mounting bracket V2A steel, nylon dowel, spacer sleeve brass nickel plated, screws, washers, snorkel washer, nut		



The guarantee period for the product is 5 years and begins on the day of shipment.

Reference is the date of the delivery bill. The guarantee period may differ for accessories.