



BERgamo HP

Linear Luminaire - anodised aluminium - Light colour green -
 Length 666mm - Outdoor

- elegant wallwasher with high lumen output for indoor and outdoor architectural area illumination
- seamless and shadowless alignment possible, several luminaires operable with one controller
- Impact resistance: IK10
- Temperature monitoring. Automatic dimming of the LEDs in the case of overheating to protect from damage
- anodised aluminium housing, coloured eloxal on request
- outdoor: high end full encapsulation for excellent protection (IP 67/68*)



LATERAL VIEW OF THE TWO VARIETIES



LIGHT DATA

	62671317	62671326	62671337	62671355
Version	without glare shield with straight cover			
Version	63671317	63671326	63671337	63671355
Version	with glare shield with straight cover			
LED beam angle	17 °	26 °	37 °	43x16 °
Typ. luminous flux	3120 lm			
Dominating wavelength	523 nm			
Efficiency	65 lm/W			
Energy efficiency class	A			
Number of LEDs	24			

POWER DATA

	62671317	62671326	62671337	62671355
Constant voltage/Constant current	CV			
Operating voltage	24 V DC			
Typ. current consumption	1500 mA			
Typ. power	36 W			
Lifetime L70	>60.000 h			

FURTHER DATA

	62671317	62671326	62671337	62671355
Material	Aluminium			
Finish	anodised			
Color of material	aluminium			
Type of protection	IP 67;IP 68			
Indoor/Outdoor	Outdoor			
Umgebungstemperatur Ta max	55 ° C			
Length	666 mm			
Width	28 mm			
Height	39 mm			
Weight	700 gr			
Cable length/cable finishing	5m cable with free wire ends			
Remarks	Impact resistance: IK10 without mounting bracket and cantilever arm			

Maximum values at Ta=25°C

ACCESSORIES

	62399487	62399488	62399489
Description	mounting bracket standard, for mounting in ceiling and floor, incl. 2 screws and 2 dowels, distance to wall 15 mm	cantilever arm, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 65 mm	cantilever arm long, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 201 mm
Material	304 stainless steel		
Length	73,7 mm	71,4 mm	206,3 mm
Width	58 mm		
Height	20,4 mm	55,5 mm	85,5 mm
Remarks	Mounting bracket V2A steel, nylon dowel, spacer sleeve brass nickel plated, screws, washers, snorkel washer, nut		



*Tested by TÜV Rheinland on 03.2013 - Test specification: EN60598-1: 2008 + A11: 2009

Test conditions: water depth 5 m/testing time 60 min.

When planning to use the luminaire with continuous immersion, ambient conditions must be previously defined between manufacturer and user!