



# BERgamo HP

## Linear Luminaire - anodised aluminium - RGBW - Length 666mm - Outdoor

- elegant wallwasher with high lumen output for indoor and outdoor architectural area illumination
- seamless and shadowless alignment possible, several luminaires operable with one controller
- Impact resistance: IK10
- Temperature monitoring. Automatic dimming of the LEDs in the case of overheating to protect from damage
- anodised aluminium housing, coloured eloxal on request
- outdoor: high end full encapsulation for excellent protection (IP 67/68\*)



### LATERAL VIEW OF THE TWO VARIETIES



### LIGHT DATA

	62673617	62673626	62673637	62673655	63673617	63673626	63673637	63673655
Version	ohne Blendschutz				mit Blendschutz			
Light color	RGBW							
LED beam angle	17 °	26 °	37 °	43x16 °	17 °	26 °	37 °	43x16 °
Typ. luminous flux	3100 lm							
Efficiency	53 lm/W							
Energy efficiency class	B							
Number of LEDs	24							

## POWER DATA

	62673617	62673626	62673637	62673655	63673617	63673626	63673637	63673655
Constant voltage/Constant current	CC							
Operating current	4x700 mA							
Typ. power	59 W							
Lifetime L70	>36000 h							

## FURTHER DATA

	62673617	62673626	62673637	62673655	63673617	63673626	63673637	63673655
Material	Aluminium							
Finish	anodised							
Color of material	aluminium eloxiert							
Type of protection	IP 67;IP 68							
Indoor/Outdoor	Outdoor							
Umgebungstemperatur Ta max	55 ° C							
Length	666 mm							
Width	28 mm							
Height	39 mm					54 mm		
Weight	700 gr					780 gr		
Cable length/cable finishing	5m cable with free wire ends							
Remarks	Impact resistance: IK10 without mounting bracket and cantilever arm							

Maximum values at Ta=25°C

## ACCESSORIES

	62399487	62399488	62399489
Description	mounting bracket standard, for mounting in ceiling and floor, incl. 2 screws and 2 dowels, distance to wall 15 mm	cantilever arm, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 65 mm	cantilever arm long, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 201 mm
Material	304 stainless steel		
Length	73,7 mm	71,4 mm	206,3 mm
Width	58 mm		
Height	20,4 mm	55,5 mm	85,5 mm
Remarks	Mounting bracket V2A steel, nylon dowel, spacer sleeve brass nickel plated, screws, washers, snorkel washer, nut		



\*Tested by TÜV Rheinland on 03.2013 - Test specification: EN60598-1: 2008 + A11: 2009

Test conditions: water depth 5 m/testing time 60 min.

When planning to use the luminaire with continuous immersion, ambient conditions must be previously defined between manufacturer and user!

The guarantee period for the product is 5 years and begins on the day of shipment.

Reference is the date of the delivery bill. The guarantee period may differ for accessories.