




BERgamo HP

Linear Luminaire - anodised aluminium - RGB - Length 996mm - Indoor

- elegant wallwasher with high lumen output for indoor and outdoor architectural area illumination
- seamless and shadowless alignment possible, several luminaires operable with one controller
- Impact resistance: IK10
- Temperature monitoring. Automatic dimming of the LEDs in the case of overheating to protect from damage
- anodised aluminium housing, coloured eloxal on request
- indoor: optionally with a straight plastic cover – with or without glare shield - or with a half-round cover for special protection against dust and dirt



LATERAL VIEW OF THE THREE VARIETIES



LIGHT DATA

	62903117	62903126	62903137	62903155	63903117	63903126	63903137	63903155	64903117	64903126	64903137	64903155
Light color	RGB											
LED beam angle	17 °	26 °	37 °	43x16 °	17 °	26 °	37 °	43x16 °	17 °	26 °	37 °	43x16 °
Typ. luminous flux	3140 lm											
Efficiency	58 lm/W											
Energy efficiency class	A											
Number of LEDs	36											

POWER DATA

	62903117	62903126	62903137	62903155	63903117	63903126	63903137	63903155	64903117	64903126	64903137	64903155
Constant voltage/Constant current	CV											
Operating voltage	24 V DC											
Typ. current consumption	2,25 A											
Typ. power	54 W											
Lifetime L70	>60000 h											


FURTHER DATA

	62903117	62903126	62903137	62903155	63903117	63903126	63903137	63903155	64903117	64903126	64903137	64903155
Material	Aluminium											
Finish	anodised											
Color of material	aluminium eloxiert											
Type of protection	IP 30											
Indoor/Outdoor	Indoor											
Umgebungstemperatur Ta max	55 ° C											
Length	996 mm											
Width	28 mm											
Height	39 mm				54 mm				39 mm			
Weight	1100 gr				1230 gr				1100 gr			
Cable length/cable finishing	5m cable with free wire ends											
Remarks	Impact resistance: IK10 without mounting bracket and cantilever arm											

Maximum values at Ta=25°C

ACCESSORIES

	62399487	62399488	62399489
Description	mounting bracket standard, for mounting in ceiling and floor, incl. 2 screws and 2 dowels, distance to wall 15 mm	cantilever arm, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 65 mm	cantilever arm long, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 201 mm
Material	304 stainless steel		
Length	73,7 mm	71,4 mm	206,3 mm
Width	58 mm		
Height	20,4 mm	55,5 mm	85,5 mm
Remarks	Mounting bracket V2A steel, nylon dowel, spacer sleeve brass nickel plated, screws, washers, snorkel washer, nut		



The guarantee period for the product is 5 years and begins on the day of shipment.

Reference is the date of the delivery bill. The guarantee period may differ for accessories.