




# BERgamo HP

## Linear Luminaire - anodised aluminium - RGBW - Length 996mm - Indoor

- elegant wallwasher with high lumen output for indoor and outdoor architectural area illumination
- seamless and shadowless alignment possible, several luminaires operable with one controller
- Impact resistance: IK10
- Temperature monitoring. Automatic dimming of the LEDs in the case of overheating to protect from damage
- anodised aluminium housing, coloured eloxal on request
- indoor: optionally with a straight plastic cover – with or without glare shield - or with a half-round cover for special protection against dust and dirt



### LATERAL VIEW OF THE THREE VARIETIES



### LIGHT DATA

	62983617	62983626	62983637	62983655	63983617	63983626	63983637	63983655	64983617	64983626	64983637	64983655
Light color	RGBW											
LED beam angle	17 °	26 °	37 °	43x16 °	17 °	26 °	37 °	43x16 °	17 °	26 °	37 °	43x16 °
Typ. luminous flux	4650 lm											
Efficiency	53 lm/W											
Energy efficiency class	B											
Number of LEDs	36											

## POWER DATA

	62983617	62983626	62983637	62983655	63983617	63983626	63983637	63983655	64983617	64983626	64983637	64983655
Constant voltage/Constant current	CC											
Operating current	4x700 mA											
Typ. power	89 W											
Lifetime L70	>36000 h											

## FURTHER DATA

	62983617	62983626	62983637	62983655	63983617	63983626	63983637	63983655	64983617	64983626	64983637	64983655
Material	Aluminium											
Finish	anodised											
Color of material	aluminium eloxiert											
Type of protection	IP 30											
Indoor/Outdoor	Indoor											
Umgebungstemperatur Ta max	55 ° C											
Length	996 mm											
Width	28 mm											
Height	39 mm			54 mm			39 mm					
Weight	1100 gr			1230 gr			1100 gr					
Cable length/cable finishing	5m cable with free wire ends											
Remarks	Impact resistance: IK10 without mounting bracket and cantilever arm											

Maximum values at Ta=25°C

## ACCESSORIES

	62399487	62399488	62399489
Description	mounting bracket standard, for mounting in ceiling and floor, incl. 2 screws and 2 dowels, distance to wall 15 mm	cantilever arm, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 65 mm	cantilever arm long, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 201 mm
Material	304 stainless steel		
Length	73,7 mm	71,4 mm	206,3 mm
Width	58 mm		
Height	20,4 mm	55,5 mm	85,5 mm
Remarks	Mounting bracket V2A steel, nylon dowel, spacer sleeve brass nickel plated, screws, washers, snorkel washer, nut		



The guarantee period for the product is 5 years and begins on the day of shipment.

Reference is the date of the delivery bill. The guarantee period may differ for accessories.