



BERgamo HP

Linear Luminaire - anodised aluminium - RGBW - Length 996mm - Outdoor

- elegant wallwasher with high lumen output for indoor and outdoor architectural area illumination
- seamless and shadowless alignment possible, several luminaires operable with one controller
- Impact resistance: IK10
- Temperature monitoring. Automatic dimming of the LEDs in the case of overheating to protect from damage
- anodised aluminium housing, coloured eloxal on request
- outdoor: high end full encapsulation for excellent protection (IP 67/68*)



LATERAL VIEW OF THE TWO VARIETIES



LIGHT DATA

	62993617	62993626	62993637	62993655	63993617	63993626	63993637	63993655
Version	ohne Blendschutz				mit Blendschutz			
Light color	RGBW							
LED beam angle	17 °	26 °	37 °	43x16 °	17 °	26 °	37 °	43x16 °
Typ. luminous flux	4650 lm							
Efficiency	53 lm/W							
Energy efficiency class	B							
Number of LEDs	36							

POWER DATA

	62993617	62993626	62993637	62993655	63993617	63993626	63993637	63993655
Constant voltage/Constant current	CC							
Operating current	4x700 mA							
Typ. power	89 W							
Lifetime L70	>36000 h							

FURTHER DATA

	62993617	62993626	62993637	62993655	63993617	63993626	63993637	63993655
Material	Aluminium							
Finish	anodised							
Color of material	aluminium eloxiert							
Type of protection	IP 67;IP 68							
Indoor/Outdoor	Outdoor							
Umgebungstemperatur Ta max	55 ° C							
Length	996 mm							
Width	28 mm							
Height	39 mm				54 mm			
Weight	1100 gr				1230 gr			
Cable length/cable finishing	5m cable with free wire ends							
Remarks	Impact resistance: IK10 without mounting bracket and cantilever arm							

Maximum values at Ta=25°C

ACCESSORIES

	62399487	62399488	62399489
Description	mounting bracket standard, for mounting in ceiling and floor, incl. 2 screws and 2 dowels, distance to wall 15 mm	cantilever arm, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 65 mm	cantilever arm long, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 201 mm
Material	304 stainless steel		
Length	73,7 mm	71,4 mm	206,3 mm
Width	58 mm		
Height	20,4 mm	55,5 mm	85,5 mm
Remarks	Mounting bracket V2A steel, nylon dowel, spacer sleeve brass nickel plated, screws, washers, snorkel washer, nut		



*Tested by TÜV Rheinland on 03.2013 - Test specification: EN60598-1: 2008 + A11: 2009

Test conditions: water depth 5 m/testing time 60 min.

When planning to use the luminaire with continuous immersion, ambient conditions must be previously defined between manufacturer and user!

The guarantee period for the product is 5 years and begins on the day of shipment.

Reference is the date of the delivery bill. The guarantee period may differ for accessories.