

AQUALUC C:URVE Accessories


You have various possibilities to secure the AQUALUC. Either with support profiles for linear lines or using retaining brackets, double-sided adhesive tape or construction glue for flexible installations.

The mounting profile 40500037/40500038 enables the AQUALUC to expand linearly, as it is not clamped in the profile but only held by it ("floating"). **Expansion and compression of the Aqualuc** due to self-heating and larger temperature differences during installation outdoors **are thus minimised, which has a positive effect on the service life.**

Please observe the installation and safety instructions at <https://www.barthelme.de/content/en/manuals.aspx> !

MOUNTING PROFILES

	40500033	40500034	40500037	40500038
Description	AQUALUC C:URVE (10 x 18,5 mm) aluminium mounting profile, anodised		AQUALUC C:URVE (10 x 18,5 mm); not gripping mounting profile, aluminium, anodized	
Material	Aluminium 6063			
Length	1000 mm	2000 mm		3000 mm
Width	15,3 mm		14,6 mm	
Height	16,3 mm		25 mm	
Remarks			The Aqualuc is enclosed and can move freely. Strain and compression of the light line are avoided in the event of temperature fluctuations.	




	40500071	40500072
Description	AQUALUC C:URVE (10 x 18.5 mm) mounting profile, PC plastic, UV resistant	
Material	Plastics	
Length	1000 mm	2000 mm
Width	15,3 mm	
Height	16,3 mm	




BRACKETS

	40500035	40500036
Description	AQUALUC C:URVE (10 x 18,5 mm) aluminium bracket set, 10 pieces 5 cm, 10 screws, 10 dowels	AQUALUC C:URVE (10 x 18,5 mm) bracket set, 10 pieces stainless steel 316L, 10 screws, 10 dowels
Material	Aluminium 6063	316L stainless steel
Length	50 mm	20 mm
Width	15,3 mm	11,5 mm
Height	16,3 mm	16,5 mm
Remarks	Diameter hole: 2.9 mm	Diameter hole: 6 mm



ACCESSORIES

	30033019	40100111	63500024	63500033
Description	heat resistant double-sided tape, with excellent adhesive properties	dismounting tool, minimizes the mechanical stress on the product when removing	Technical Vaseline, high purity, chemically neutral, 80 g tube, suitable for all mounting profiles	Silicone adhesive and sealant, one-component, transparent, cartridge 290 ml
Material	Acryl	Poly lactide PLA		
Length	33000 mm	210 mm		
Width	9 mm	8 mm		
Height	0,4 mm	62 mm		
Remarks	33 m x 9 mm		For the assembly of the AQUALUC absolutely recommended	not suitable for PC-plastic profiles



NOTE

Press marks or slight scratches on profiles are production-related and do not constitute a defect.