

## AQUALUC mini Accessories

You have various possibilities to secure the AQUALUC. Either with support profiles for linear lines or using retaining brackets, double-sided adhesive tape or construction glue for flexible installations.

**Please observe the installation and safety instructions at <https://www.barthelme.de/content/en/manuals.aspx> !**

	40100107	40100108
<b>Description</b>	AQUALUC mini polycarbonate plastic support profile with adhesive tape, UV resistant	
<b>Material</b>	Plastics	
<b>Length</b>	1000 mm	2000 mm
<b>Width</b>	13 mm	
<b>Height</b>	9,9 mm	
<b>Fire protection class</b>	B2 (DIN 4102)	
<b>Ambient temperature</b>	-40 ~ +130 ° C	
<b>Remarks</b>	Material: Polycarbonat	



Please note that different materials can expand to different degrees when the temperature changes. This is not a product defect, but a normal physical process. In concrete terms, this means that a linear thermal linear expansion of approx. 1 mm per metre and 15 °C temperature change occurs. This additionally required expansion joint should always be included if several profiles are lined up.

If you install two profiles directly next to each other (side by side), please ensure during installation that the profiles expand or contract as the temperature fluctuates. In the case of on-site installation using screws, we recommend slotted holes so that the expansion of the area between the screws can also be compensated. The screws must not be tightened too much, so that the profile can be moved longitudinally.

	63500033
<b>Description</b>	Silicone adhesive and sealant, one-component, transparent, cartridge 290 ml
<b>Remarks</b>	not suitable for PC-plastic profiles



### DIMENSIONED DRAWING

