




BERgamo HP

Linear Luminaire - anodised aluminium - Light colour green -
 Length 336mm - Indoor

- elegant wallwasher with high lumen output for indoor and outdoor architectural area illumination
- seamless and shadowless alignment possible, several luminaires operable with one controller
- Impact resistance: IK10
- Temperature monitoring. Automatic dimming of the LEDs in the case of overheating to protect from damage
- anodised aluminium housing, coloured eloxal on request
- indoor: optionally with a straight plastic cover – with or without glare shield - or with a half-round cover for special protection against dust and dirt



LATERAL VIEW OF THE THREE VARIETIES



LIGHT DATA

	62331317	62331326	62331337	62331355
Version	without glare shield with straight cover			
Cut	63331317	63331326	63331337	63331355
	with glare shield with straight cover			
Version	64331317	64331326	64331337	64331355
	without glare shield with semicircular cover			
LED beam angle	17 °	26 °	37 °	43x16 °
Typ. luminous flux	1560 lm			
Dominating wavelength	523 nm			
Efficiency	65 lm/W			
Energy efficiency class	A			
Number of LEDs	12			

POWER DATA

	62331317	62331326	62331337	62331355
Constant voltage/Constant current	CV			
Operating voltage	24 V DC			
Typ. current consumption	750 mA			
Typ. power	18 W			
Lifetime L70	>60.000 h			

FURTHER DATA

	62331317	62331326	62331337	62331355
Material	Aluminium			
Finish	anodised			
Color of material	aluminium			
Type of protection	IP 30			
Indoor/Outdoor	Indoor			
Umgebungstemperatur Ta max	55 ° C			
Length	336 mm			
Width	28 mm			
Height	39 mm			
Weight	350 gr			
Cable length/cable finishing	5m cable with free wire ends			
Remarks	Impact resistance: IK10 without mounting bracket and cantilever arm			

Maximum values at Ta=25°C

ACCESSORIES

	62399487	62399488	62399489
Description	mounting bracket standard, for mounting in ceiling and floor, incl. 2 screws and 2 dowels, distance to wall 15 mm	cantilever arm, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 65 mm	cantilever arm long, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 201 mm
Material	304 stainless steel		
Length	73,7 mm	71,4 mm	206,3 mm
Width	58 mm		
Height	20,4 mm	55,5 mm	85,5 mm
Remarks	Mounting bracket V2A steel, nylon dowel, spacer sleeve brass nickel plated, screws, washers, snorkel washer, nut		

