




BERgamo HP

Linear Luminaire - anodised aluminium - Light colour blue -
 Length 336mm - Indoor

- elegant wallwasher with high lumen output for indoor and outdoor architectural area illumination
- seamless and shadowless alignment possible, several luminaires operable with one controller
- Impact resistance: IK10
- Temperature monitoring. Automatic dimming of the LEDs in the case of overheating to protect from damage
- anodised aluminium housing, coloured eloxal on request
- indoor: optionally with a straight plastic cover – with or without glare shield - or with a half-round cover for special protection against dust and dirt



LATERAL VIEW OF THE THREE VARIETIES



LIGHT DATA

| | 62331417 | 62331426 | 62331437 | 62331455 |
|--------------------------------|--|----------|----------|----------|
| Version | without glare shield with straight cover | | | |
| Cut | 63331417 | 63331426 | 63331437 | 63331455 |
| | with glare shield with straight cover | | | |
| Version | 64331417 | 64331426 | 64331437 | 64331455 |
| | without glare shield with semicircular cover | | | |
| LED beam angle | 17 ° | 26 ° | 37 ° | 43x16 ° |
| Typ. luminous flux | 660 lm | | | |
| Dominating wavelength | 470 nm | | | |
| Efficiency | 28 lm/W | | | |
| Energy efficiency class | B | | | |
| Number of LEDs | 12 | | | |

POWER DATA

| | 62331417 | 62331426 | 62331437 | 62331455 |
|-----------------------------------|-----------|----------|----------|----------|
| Constant voltage/Constant current | CV | | | |
| Operating voltage | 24 V DC | | | |
| Typ. current consumption | 750 mA | | | |
| Typ. power | 18 W | | | |
| Lifetime L70 | >60.000 h | | | |

FURTHER DATA

| | 62331417 | 62331426 | 62331437 | 62331455 |
|------------------------------|--|----------|----------|----------|
| Material | Aluminium | | | |
| Finish | anodised | | | |
| Color of material | aluminium | | | |
| Type of protection | IP 30 | | | |
| Indoor/Outdoor | Indoor | | | |
| Umgebungstemperatur Ta max | 55 ° C | | | |
| Length | 336 mm | | | |
| Width | 28 mm | | | |
| Height | 39 mm | | | |
| Weight | 350 gr | | | |
| Cable length/cable finishing | 5m cable with free wire ends | | | |
| Remarks | Impact resistance: IK10 without mounting bracket and cantilever arm | | | |

Maximum values at Ta=25°C

ACCESSORIES

| | 62399487 | 62399488 | 62399489 |
|-------------|---|--|--|
| Description | mounting bracket standard, for mounting in ceiling and floor, incl. 2 screws and 2 dowels, distance to wall 15 mm | cantilever arm, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 65 mm | cantilever arm long, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 201 mm |
| Material | 304 stainless steel | | |
| Length | 73,7 mm | 71,4 mm | 206,3 mm |
| Width | 58 mm | | |
| Height | 20,4 mm | 55,5 mm | 85,5 mm |
| Remarks | Mounting bracket V2A steel, nylon dowel, spacer sleeve brass nickel plated, screws, washers, snorkel washer, nut | | |

