



BERgamo HP

Linear Luminaire - anodised aluminium - Light colour white -
 Length 666mm - Outdoor

- elegant wallwasher with high lumen output for indoor and outdoor architectural area illumination
- seamless and shadowless alignment possible, several luminaires operable with one controller
- Impact resistance: IK10
- Temperature monitoring. Automatic dimming of the LEDs in the case of overheating to protect from damage
- anodised aluminium housing, coloured eloxal on request
- outdoor: high end full encapsulation for excellent protection (IP 67/68*)



LATERAL VIEW OF THE TWO VARIETIES



LIGHT DATA

	62672617	62672626	62672637	62672655	62672817	62672826	62672837	62672855	62673317	62673326	62673337	62673355
Version	ohne Blendschutz											
dimmbare	dimmbare											
	63672617	63672626	63672637	63672655	63672817	63672826	63672837	63672855	63673317	63673326	63673337	63673355
Version	mit Blendschutz											
Typ. color temperature	4000 K				2700 K				3000 K			
Light color	cold white				warm white				white			
LED beam angle	17 °	26 °	37 °	43x16 °	17 °	26 °	37 °	43x16 °	17 °	26 °	37 °	43x16 °
Typ. luminous flux	3960 lm				3560 lm				3760 lm			
Efficiency	110 lm/W				99 lm/W				104 lm/W			
Energy efficiency class	A+											
Typ. color rendering index	83											
SDCM MacAdam	3											
Number of LEDs	24											

POWER DATA

	62672617	62672626	62672637	62672655	62672817	62672826	62672837	62672855	62673317	62673326	62673337	62673355
Constant voltage/Constant current	CV											
Operating voltage	24 V DC											
Typ. power	36 W											
Lifetime L70	>36000 h											

FURTHER DATA

	62672617	62672626	62672637	62672655	62672817	62672826	62672837	62672855	62673317	62673326	62673337	62673355
Material	Aluminium											
Finish	anodised											
Color of material	aluminium eloxiert											
Type of protection	IP 67;IP 68											
Indoor/Outdoor	Outdoor											
Umgebungstemperatur Ta max	55 ° C											
Length	666 mm											
Width	28 mm											
Height	39 mm											
Weight	700 gr											
Cable length/cable finishing	5m cable with free wire ends											
Remarks	Impact resistance: IK10 without mounting bracket and cantilever arm											

Maximum values at Ta=25°C

ACCESSORIES

	62399487	62399488	62399489
Description	mounting bracket standard, for mounting in ceiling and floor, incl. 2 screws and 2 dowels, distance to wall 15 mm	cantilever arm, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 65 mm	cantilever arm long, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 201 mm
Material	304 stainless steel		
Length	73,7 mm	71,4 mm	206,3 mm
Width	58 mm		
Height	20,4 mm	55,5 mm	85,5 mm
Remarks	Mounting bracket V2A steel, nylon dowel, spacer sleeve brass nickel plated, screws, washers, snorkel washer, nut		



*Tested by TÜV Rheinland on 03.2013 - Test specification: EN60598-1: 2008 + A11: 2009

Test conditions: water depth 5 m/testing time 60 min.

When planning to use the luminaire with continuous immersion, ambient conditions must be previously defined between manufacturer and user!

The guarantee period for the product is 5 years and begins on the day of shipment.

Reference is the date of the delivery bill. The guarantee period may differ for accessories.