




# BERgamo HP

Linear Luminaire - anodised aluminium - Light colour green -  
 Length 996mm - Indoor

- elegant wallwasher with high lumen output for indoor and outdoor architectural area illumination
- seamless and shadowless alignment possible, several luminaires operable with one controller
- Impact resistance: IK10
- Temperature monitoring. Automatic dimming of the LEDs in the case of overheating to protect from damage
- anodised aluminium housing, coloured eloxal on request
- indoor: optionally with a straight plastic cover – with or without glare shield - or with a half-round cover for special protection against dust and dirt



## LATERAL VIEW OF THE THREE VARIETIES



## LIGHT DATA

	62981317	62981326	62981337	62981355
Version	without glare shield with straight cover			
Cut	63981317	63981326	63981337	63981355
	with glare shield with straight cover			
Version	64981317	64981326	64981337	64981355
	without glare shield with semicircular cover			
LED beam angle	17 °	26 °	37 °	43x16 °
Typ. luminous flux	4680 lm			
Dominating wavelength	523 nm			
Efficiency	65 lm/W			
Energy efficiency class	A			
Number of LEDs	36			

## POWER DATA

	62981317	62981326	62981337	62981355
Constant voltage/Constant current			CV	
Operating voltage			24 V DC	
Typ. current consumption			2,25 A	
Typ. power			54 W	
Lifetime L70			>60.000 h	

## FURTHER DATA

	62981317	62981326	62981337	62981355
Material			Aluminium	
Finish			anodised	
Color of material			aluminium	
Type of protection			IP 30	
Indoor/Outdoor			Indoor	
Umgebungstemperatur Ta max			55 ° C	
Length			996 mm	
Width			28 mm	
Height			39 mm	
Weight			1100 gr	
Cable length/cable finishing			5m cable with free wire ends	
Remarks			Impact resistance: IK10 without mounting bracket and cantilever arm	

Maximum values at Ta=25°C

## ACCESSORIES

	62399487	62399488	62399489
Description	mounting bracket standard, for mounting in ceiling and floor, incl. 2 screws and 2 dowels, distance to wall 15 mm	cantilever arm, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 65 mm	cantilever arm long, for mounting on walls, incl. 2 screws and 2 dowels, distance to wall 201 mm
Material		304 stainless steel	
Length	73,7 mm	71,4 mm	206,3 mm
Width		58 mm	
Height	20,4 mm	55,5 mm	85,5 mm
Remarks	Mounting bracket V2A steel, nylon dowel, spacer sleeve brass nickel plated, screws, washers, snorkel washer, nut		

