



PISA 1.2 SAUNA

- » dimmbare, hochwertige LED-Trockensaunaleuchte
 - » geeignet für Umgebungstemperaturen an der Blende bis 100 °C
 - » gefrästes Gehäuse aus Aluminium, eloxiert - wahlweise mit V2A- oder V4A-Edelstahlblenden
 - » als integrierte Ambient-Beleuchtung einsetzbar
 - » CV-Version in den Weißtönen 2700 K, 3000 K und 4000 K sowie mit 5 wählbaren Abstrahlwinkeln erhältlich
 - » CC-Version für RGB- und RGBW-Anwendungen
 - » mit integrierter Membran zur Vermeidung von Betauung und Verschmutzung durch Druckausgleich
 - » inkl. 5 m-Anschlusskabel mit freien Drahtenden
 - » CV-Version optional mit M8- oder M12-Steckverbinder ausrüstbar
 - » Lebensdauerabschätzung L70 bei Ta < 45 °C: > 51.400 h (> 60.000 h RGB(W))
- » dimmable, high quality LED spot for dry sauna applications
 - » suitable for ambient temperatures on the shield up to 100 °C
 - » milled aluminium housing, anodised - with either 304 or 316L stainless steel shield
 - » for use as integrated ambient lighting
 - » available as CV version in the white tones 2700 K, 3000 K, and 4000 K plus five optional beam angles
 - » available as CC version for RGB and RGBW applications
 - » with integrated membrane for prevention of condensation and contamination through pressure compensation
 - » incl. 5 m connection cable with free wire ends
 - » CV version optional fitting with M8 or M12 connector
 - » estimated lifetime L70 at Ta < 45 °C: > 51,400 h (> 60,000 h RGB(W))

PISA 1.2 SAUNA 12/24V

BLENDE / EINBAU | SHIELD / MOUNTING: Ø 54,5 mm / Ø 40 mm



Artikel-Nr. ¹ Item no.	Lichtfarbe Light color	Typ. Farbtemp. Typ. color temp.	Typ Leistung Typ. power	Typ. Lichtstrom Typ. light output	Lumen/Watt	Typ. CRI	Abstrahlwinkel Beam angle	EEK EEC
627#28112	warmweiß 827 warm white	2700 K		220 lm	85 lm/W	83		
627#33112	weiß 830 white	3000 K	2,6 W	230 lm	88 lm/W	83	12°	A+
627#26112	kaltweiß 840 cool white	4000 K		240 lm	92 lm/W	83		
627#28202	warmweiß 827 warm white	2700 K		220 lm	85 lm/W	83		
627#33202	weiß 830 white	3000 K	2,6 W	230 lm	88 lm/W	83	21°	A+
627#26202	kaltweiß 840 cool white	4000 K		240 lm	92 lm/W	83		
627#28322	warmweiß 827 warm white	2700 K		220 lm	85 lm/W	83		
627#33322	weiß 830 white	3000 K	2,6 W	230 lm	88 lm/W	83	34°	A+
627#26322	kaltweiß 840 cool white	4000 K		240 lm	92 lm/W	83		
627#28472	warmweiß 827 warm white	2700 K		220 lm	85 lm/W	83		
627#33472	weiß 830 white	3000 K	2,6 W	230 lm	88 lm/W	83	44° x 9°	A+
627#26472	kaltweiß 840 cool white	4000 K		240 lm	92 lm/W	83		

¹ # = 3 = Blende V2A-Edelstahl || # = 4 = Blende: V4A-Edelstahl, gebürstet |
= 3 = shield: 304 stainless steel || # = 4 = shield: 316L stainless steel, brushed

LEUCHTEN
LUMINAIRES

PISA 1.2 SAUNA

BLENDE / EINBAU | SHIELD / MOUNTING: Ø 54,5 mm / Ø 40 mm



Artikel-Nr. ¹ Item no.	Lichtfarbe Light color	Typ. Farbtemp. Typ. color temp.	Max. Leistung Max. power	Typ. Lichtstrom Typ. light output	Lumen/Watt	Abstrahlwinkel Beam angle	EEK EEC
627#31252	RGB	RGB	3 W	145 lm	48 lm/W	25°	A+
627#36252	RGBW	RGBW	4,1 W	225 lm	55 lm/W	25°	A+

¹ # = 3 = Blende V2A-Edelstahl || # = 4 = Blende: V4A-Edelstahl, gebürstet |
= 3 = shield: 304 stainless steel || # = 4 = shield: 316L stainless steel, brushed

